

HORIZONTAL ROLLER WINDOWS 800 SERIES

FEATURES & BENEFITS

- Brass tandem rollers for dependable long-life operation
- XO or OX configurations
- Egress connector bar provides single-step operation
- Die cast sash lock for strength and security
- 2¾" nominal frame depth
- Weep slots for efficient water drainage

PRODUCT SPECIFICATIONS - HR810

TEST TYPE	FRAME TYPE & MAXIMUM SIZE	FRAME DEPTH	POSITIVE DESIGN PRESSURE	NEGATIVE DESIGN PRESSURE	WATER RESISTANCE	AIR INFILTRATION	GLAZING	TESTS COMPLETED
LARGE MISSILE	FLANGE: 74" x 63"	2¾"	+90	-110	13.5 psf	0.29 @ 1.57	<ul style="list-style-type: none"> • 7/16" SGP Laminated (Heat Strengthened/Heat Strengthened) 	<ul style="list-style-type: none"> • Miami-Dade NOA: 08-0408.03 • Florida Product Approval: FL-242 • Forced Entry Resistance: AAMA 1302.5
SMALL MISSILE	FLANGE: 74" x 63"	2¾"	+90	-150	13.5 psf	0.29 @ 1.57	<ul style="list-style-type: none"> • 7/16" PVB Laminated (Annealed/Annealed) or (Heat Strengthened/Heat Strengthened) • 7/16" SGP Laminated (Heat Strengthened/Heat Strengthened) 	<ul style="list-style-type: none"> • Miami-Dade NOA: 07-0829.08 • Florida Product Approval: FL-242 • Forced Entry Resistance: AAMA 1302.5
NON-IMPACT	FLANGE: 74" x 63"	2¾"	+90	-150	13.5 psf	0.21 @ 1.57	<ul style="list-style-type: none"> • 3/16" Monolithic (Tempered) • 1/4" Monolithic (Tempered) 	<ul style="list-style-type: none"> • Miami-Dade NOA: 07-0829.09 • Florida Product Approval: FL-242 • Forced Entry Resistance: AAMA 1302.5